

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/NO05/000102

International filing date: 21 March 2005 (21.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: NO
Number: 20041347
Filing date: 31 March 2004 (31.03.2004)

Date of receipt at the International Bureau: 05 April 2005 (05.04.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



KONGERIKET NORGE
The Kingdom of Norway

Bekreftelse på patentsøknad nr
Certification of patent application no

▽
2004 1347

▷ Det bekreftes herved at vedheftede dokument er nøyaktig utskrift/kopi av ovennevnte søknad, som opprinnelig inngitt 2004.03.31

▷ *It is hereby certified that the annexed document is a true copy of the above-mentioned application, as originally filed on 2004.03.31*

2005.03.23

Line Reum

Line Reum
Saksbehandler



**Søknad om patent**

2004 -03- 31

Ferdig utfylt skjema sendes til adressen nedenfor. Vennligst ikke heft sammen sidene.
Vi ber om at blankettene utfylles *maskinelt* eller ved bruk av *blokkbokstaver*. Skjema for
utfylling på datamaskin kan lastes ned fra www.patentstyret.no.

Søker Den som søker om patent blir også innehaver av en eventuell rettighet. Må fylles ut!

Foretakets navn (fornavn hvis søker er person):

Telenor ASA

Etternavn (hvis søker er person):

☐ Kryss av hvis søker tidligere har vært kunde hos Patentstyret.

Oppgi gjerne kundennummer:

Adresse:

Snarøyveien 30

Postnummer:
1331Poststed:
Førnebu

Land:

☐ Kryss av hvis flere søkere er angitt i
medfølgende skjema eller på eget ark.☐ Kryss av hvis søker(ne) utfører
20 årsverk eller mindre (se veiledning).**Kontaktinfo** Hvem skal Patentstyret henvende seg til? Oppgi telefonnummer og eventuell referanse.

Fornavn til kontaktperson for fullmektig eller søker:

Bjørn

Etternavn:

Andersen



Telefon:

23327700

Referanse (maks. 30 tegn):

116093 BAN/LF



Evt. adresse til kontaktperson:

Postnummer:

Poststed:

Land:

Fullmektig Hvis du ikke har oppnevnt en fullmektig, kan du gå til neste punkt.

Foretakets navn (fornavn hvis fullmektig er person):

Onsagers AS

Etternavn (hvis fullmektig er person):

☒ Kryss av hvis fullmektig tidligere har vært kunde hos Patentstyret.

Oppgi gjerne kundennummer:

1075

Adresse:

Postnummer:

Poststed:

Land:

Oppfinder Oppfinneren skal alltid oppgis, selv om oppfinner og søker er samme person.

Oppfinnerens fornavn:

Juan Carlos López

Etternavn:

Calvet

☐ Kryss av hvis oppfinner tidligere har vært kunde hos Patentstyret.

Oppgi gjerne kundennummer:

Adresse:

Hovseterveien 66C

Postnummer:
0768Poststed:
OSLO

Land:

☒ Kryss av hvis flere oppfinnere er angitt i medfølgende skjema eller på eget ark.

SØKNAD s. 1 av 2

FLERE SØKERE

FLERE OPPFINNERE

PRIORITETER

VEILEDNING

ADRESSE

Postboks 8160 Dep.
Københavngaten 10
0033 Oslo

TELEFON

22 38 73 00
TELEFAX
22 38 73 01

BANKGIRO

8276.01.00192
ORGANISASJONSNR.
971526157 MVA**PATENTSTYRET®**
Styret for det industrielle rettsvern



... søknad om patent

SØKNAD s. 2 av 2

Tittel Gi en kort benevnelse eller tittel for oppfinnelsen (ikke over 256 tegn, inkludert mellomrom).

Tittel:
Subscriber identity module

PCT Fylles bare ut hvis denne søknaden er en videreføring av en tidligere innlevert internasjonal søknad (PCT).

Inngivelsesdato (åååå.mm.dd):

Søknadsnummer:

PCT-søknadens dato og nummer:

PCT

/

Prioritetskrav Hvis du ikke har søkt om denne oppfinnelsen tidligere (i et annet land eller i Norge) kan du gå videre til neste punkt.

Prioritet kreves på grunnlag av tidligere innlevert søknad i Norge eller utlandet:

Inngivelsesdato (åååå.mm.dd):

Landkode:

Søknadsnummer:

Opplysninger om tidligere søknad. Ved flere krav skal tidligste prioritet angis her:

☐ Flere prioritetskrav er angitt i medfølgende skjema, eller på eget ark.

Biologisk materiale Fylles bare ut hvis oppfinnelsen omfatter biologisk materiale.

Søknaden omfatter biologisk materiale. Deponeringssted og nummer må oppgis:

Deponeringssted og nummer (barnytt gjerne eget ark).

☐ Prøve av materiale skal bare utleveres til en særlig sakkyndig.

Avdelt/utskilt Hvis du ikke har søkt om patent i Norge tidligere, kan du gå videre til neste punkt.

Søknaden er avdelt eller utskilt fra tidligere levert søknad i Norge:

☐ Avdelt søknad

Dato (åååå.mm.dd):

Søknadsnummer:

☐ Utskilt søknad

Informasjon om opprinnelig søknad/innsendt tilleggsmateriale

Annet

☐ Søknaden er også levert per telefaks.

Oppgi dato (åååå.mm.dd):

☐ Jeg har fått utført forundersøkelse.

Oppgi nr (årstall - nummer - bokstav):

Vedlegg Angi hvilken dokumentasjon av oppfinnelsen du legger ved, samt andre vedlegg.

☒ Tegninger

Oppgi antall tegninger:

4

☒ Beskrivelse av oppfinnelsen

☒ Patentkrav

☐ Fullmaktsdokument(ler)

☒ Sammendrag på norsk

☐ Overdragelsesdokument(ler)

☐ Dokumentasjon av eventuelle prioritetskrav (prioritetsbevis)

☐ Erklæring om retten til oppfinnelsen

☐ Oversettelse av internasjonal søknad (kun hvis PCT-felt over er fylt ut)

☒ Annet: Bes gransket på bakgrunn av engelsk tekst

Dato/underskrift Sjekk at du har fylt ut punktene under «Søker», «Oppfinner» og «Vedlegg». Signer søknaden.

Sted og dato (blokkbokstaver):
OSLO, 31. MARS 2004

Signatur:

Navn i blokkbokstaver:

ONSAERS AS

Lise Fredhjem

NBI Søknadsavgiften vil bli fakturert for alle søknader (dvs. at søknadsavgiften ikke skal følge søknaden).
Betalingsfrist er ca. 1 måned, se faktura.



PATENTSTYRET®
Styret for det industrielle rettsvern

2004 -03- 3 1

Vedleggsskjema:

www.patentstyret.no



Flere oppfinnere

Dette skjemaet benyttes som vedlegg til patentsøknaden for å oppgi flere oppfinnere. **NB! Gi hver oppfinner et nummer.** Personen oppgitt på søknadsskjemaet vil alltid bli registrert som nr. 01. Første angivelse på dette skjema vil være oppfinner 02. Skjema for utfylling på datamaskin kan lastes ned fra www.patentstyret.no.

▶ **Referanse** Gjentag referansen fra «kontaktinfo», eventuelt søkerens navn, som angitt på søknadsskjemaets første side. Må fylles ut!

Referanse:
116093 BAN/LF

▼ **Oppfinner nr:** 2

Fornavn og mellomnavn:
Josef

Etternavn:
Noll

☐ Oppfinner har tidligere vært kunde hos Patentstyret.

Oppgi gjerne kundennummer:

Adresse:
Linjeveien 6

Postnummer:
1084

Poststed:
Oslo

Land:

▼ **Oppfinner nr:**

Fornavn og mellomnavn:

Etternavn:

☐ Oppfinner har tidligere vært kunde hos Patentstyret.

Oppgi gjerne kundennummer:

Adresse:

Postnummer:

Poststed:

Land:

▼ **Oppfinner nr:**

Fornavn og mellomnavn:

Etternavn:

☐ Oppfinner har tidligere vært kunde hos Patentstyret.

Oppgi gjerne kundennummer:

Adresse:

Postnummer:

Poststed:

Land:

▼ **Oppfinner nr:**

Fornavn og mellomnavn:

Etternavn:

☐ Oppfinner har tidligere vært kunde hos Patentstyret.

Oppgi gjerne kundennummer:

Adresse:

Postnummer:

Poststed:

Land:

NB! Ved behov for mer plass benyttes flere skjema eller eget ark.

FLERE OPPFINNERE



PATENTSTYRET®
Styret for det industrielle rettsvern

2004 -03- 3 1

ban/ban

Applicant: Telenor ASA
Snarøyveien 30
1331 FORNEBU

Agent: ONSAGERS AS
Postboks 6963 St. Olavs plass
N-0130 OSLO

Inventors: Juan Carlos López Calvet
Hovseterveien 66C
N-0768 OSLO

Josef Noll
Linjeveien 6
N-1084 OSLO

Title: Subscriber identity module

Technical field

The present invention relates in general to mobile communication, wireless security and authentication. More specifically, the invention relates to a subscriber identity module for a mobile communication terminal, and a mobile communication terminal comprising such a subscriber identity module. The invention also relates to a method for providing secure data communication between a subscriber identity module and an external communication device, for execution by such a subscriber identity module, and to uses of a subscriber identity module or a mobile terminal equipped with such a module for authentication purposes.

Background of the invention

A subscriber identity module, or SIM card, is a removable module for use with mobile communication terminals, such as GSM mobile telephones. The SIM card contains subscriber specific data and is, in use, accessible by the central processing unit of the mobile terminal. The SIM card typically also comprises features for authenticating a user/subscriber. The SIM card includes a processing unit, a memory device and I/O devices for communication with the processing unit of the mobile terminal. The memory device contains a subscriber authentication key and computer program instructions for causing the SIM card processing unit to authenticate the user/subscriber.

WO-03/081934 discloses a mobile telephone provided with a SIM card. The mobile telephone is also provided with an RFID tag for authentication purposes. User-specific, interrogatable information is written into the RFID tag by means of the mobile telephone's processing unit. As the RFID tag is attached to the mobile telephone, only a mobile telephone having this built-in feature can be used for authentication.

WO-98/58509 discloses a mobile phone provided with a SIM card. The SIM card is further provided with a wireless interface or communication module, providing data transmission between the SIM card and an external device such as another SIM card in another mobile telephone, a computer or a cash register. This related background art provides for a separate communication channel between the external device and the SIM card. However, the publication apparently does not indicate a solution for making the SIM card interrogatable by an external interrogating device.

None of the publications appear to disclose a simple, effective and reliable solution for using the SIM card as a remotely activated authentication device.

None of the publications appear to disclose a simple, effective and reliable method for providing secure wireless data communication between the subscriber identity module and an external interrogating device.

Summary of the invention

An objective of the present invention is to provide a subscriber identity module, a mobile terminal and a method for providing secure data communication between a subscriber identity module and an external interrogating device, whereby at least
5 some of the above mentioned drawbacks of the related background art are overcome.

In accordance with a first aspect of the present invention, there is provided a subscriber identity module as indicated in the appended independent claim 1.

In accordance with a second aspect of the present invention, there is provided a
10 mobile communication terminal as indicated in the appended independent claim 11.

In accordance with a third aspect of the present invention, there is provided a method for providing secure data communication between a subscriber identity module and an interrogating device, as indicated in the appended independent claim
15 15.

The invention also relates to the use of a subscriber identity module as an authentication token, as indicated in claims 8-10.

The invention also relates to the use of a mobile communication terminal as an authentication token, as indicated in claims 12-14.

Further advantageous embodiments of the invention are set forth in the dependent
20 claims.

Additional features and principles of the present invention will be recognized from the detailed description below.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of
25 the invention, as claimed.

Brief description of the drawings

The accompanying drawings illustrate a preferred embodiment of the invention. In the drawings,

30 Fig. 1 is a schematic block diagram illustrating a first embodiment of a subscriber identity module according to the invention,

Fig. 2 is a schematic block diagram illustrating a second embodiment of a subscriber identity module according to the invention,

Fig. 3 is a schematic block diagram illustrating a system for merging RFID and mobile communication services, enabled by the present invention, and

Fig. 4 is a flowchart illustrating a method according to the invention

Detailed description of the invention

- 5 Fig. 1 is a schematic block diagram illustrating a first embodiment of a subscriber identity module according to the invention.

Fig. 1 illustrates a "bi-card" embodiment, wherein the SIM card 100 comprises separate processing devices, memory devices and I/O devices for the regular SIM functionality and the RFID functionality, respectively.

- 10 The SIM card 100 is arranged for use with a mobile communication terminal (not illustrated) such as a GSM enabled mobile telephone. The SIM card 100 comprises a processing device 110, a memory device 120, an I/O device 130, corresponding to a regular SIM controller 108 with regular SIM functionality.

- 15 The I/O device 130 comprises an interface between the SIM card and the mobile communication terminal, typically including electric connections provided on the surface of the SIM card.

The memory device 120 may comprise volatile and non-volatile memory portions, such as, e.g., RAM, ROM, EEPROM, and Flash memory.

- 20 The SIM card 100 also comprises a wireless communication device 140, in particular an interrogatable transponder 140.

- 25 The interrogatable transponder 140 is an active RFID tag. The transponder 140 is operatively controllable by the processing device 110, indicated by the line referred to by I/O. This communication line between the processing unit 110 and the transponder 140 enables the SIM card 100 to trigger events in the RFID tag and vice versa. It could also transmit certain amounts of data.

In particular, the power of the transponder 140 is controlled by the processing device 110, giving the possibility of turning the tag on and off as desired, operatively controlled by the processing device 110.

- 30 More specifically, the transponder may be operatively enabled or disabled, controlled by an on/off signal provided by the mobile communication terminal via the I/O device 130.

In one embodiment, the on/off signal is provided by a user via a user interface, such as a keyboard, in the mobile terminal. In another embodiment, the on/off signal is provided to the mobile communication terminal by a mobile communication

operator, in particular by a command transmitted to the mobile communication terminal by the operator.

5 In either case, the resulting remote enabling/disabling function of the RFID tag involves a security improvement, as the existing problem of tracing or copying continuously activated RFID tags may be overcome or reduced.

The transponder 140 comprises identification data contained in a memory 144. The identification data may be configured or set by the processing device 110.

In particular, the identification data is provided to the transponder by the mobile communication terminal via the I/O device 130.

10 The identification data is preferably transmitted to the mobile communication terminal by a mobile communication operator.

By this feature, the identification data stored in the RFID tag may be changed or re-written with new data supplied and transmitted by the mobile communication operator. This leads to the useful result that if the RFID tag is illegally/fraudulently
15 copied, the operator will have the possibility of writing a new ID into the RFID tag without having to physically change the SIM card.

The memory 144 may comprise volatile and non-volatile memory portions, such as, e.g., RAM, ROM, EEPROM, and Flash memory.

20 When the transponder 140 is interrogated by an external interrogating RF device (not illustrated), the transponder 140 is arranged to transmit, via the antenna 150, a RF signal coded with the identification data contained in the memory 144.

Fig. 2 is a schematic block diagram illustrating a second embodiment of a subscriber identity module according to the invention.

25 This embodiment mainly corresponds to the embodiment illustrated in fig. 1. However, the transponder comprises an antenna, and the RFID transponder functionality is implemented by means of the processing device, the memory device and the I/O device that are included in the subscriber identity module, i.e. the controller components also used for the regular SIM functionality.

30 Fig. 2 thus illustrates a "hybrid-card" embodiment, wherein the SIM card 200 comprises a processing device 210, memory devices 220 and I/O devices 230 which are shared between the regular SIM functionality and the RFID functionality.

The SIM card 200 is arranged for use with a mobile communication terminal (not illustrated) such as a GSM enabled mobile telephone.

The memory device 220 may comprise volatile and non-volatile memory portions, such as, e.g., RAM, ROM, EEPROM, and Flash memory.

5 The SIM card 200 also comprises a wireless communication device 140, in particular an interrogatable transponder 140, comprising an antenna 250 and the RFID functionality provided by the processing device 210, the memory devices 220 and the I/O devices 230.

The interrogatable transponder 240 constitutes an active RFID tag, operatively controllable by the processing device 210.

10 The transponder 240 comprises identification data contained in the memory 220. The identification data may be configured or set by the processing device 210.

When the transponder 240 is interrogated by an external interrogating RF device (not illustrated), the transponder 240 is arranged to transmit, via the antenna 250, a RF signal coded with the identification data contained in the memory 220.

15 This second embodiment is made possible since the basic architecture of both active RFID tags and SIM cards are so similar. This embodiment proposes a slightly more powerful SIM card with an external RFID antenna. In this case there is no need for communication between two separate cards or modules.

Fig. 3 is a schematic block diagram illustrating a system for merging RFID and mobile communication services, enabled by the present invention.

20 A mobile terminal 300, such as a mobile telephone 300, is provided with a subscriber identity module as disclosed above.

The mobile terminal 300 brings many new opportunities by merging the services typically provided by RFID tags with the infrastructure provided by GSM.

25 The idea is that events initiated by the RFID will trigger events in the mobile phone and its services, and vice versa.

Adopting the RFID technology in the SIM cards used in mobile phones avoids many practical problems that IrDA and Bluetooth have, such as pairing and alignment, bringing a fast, easy and secure way to wirelessly interact with other systems.

Fig. 4 is a flow chart illustrating a method according to the invention.

30 The method is a Public Key Infrastructure (PKI) based process for execution by a subscriber identity module, i.e. for execution by the processing device in such a subscriber identity module, according to the invention. The purpose of the method is to provide secure data communication between the subscriber identity module and

an external interrogating device, such as, e.g., a RFID reader (an RFID communication/interrogation device) of a door access system.

5 The method utilizes a private key stored in SIM card with the purpose of providing a secure communication between the external communication device and the RFID transponder included in the SIM card. This means that the RFID transponder and thus the RFID enabled SIM card can make use of the entire PKI infrastructure that is already behind the SIM card to increase the communication security between the RFID tag and the reader.

10 When a RFID transponder identifies itself to an external reader, the reader will then have enough information to retrieve the correspondent mobile phone's public key in order to start a communication session with the tag and possibly exchange a shared key to encrypt further communication between the tag and the reader.

15 The subscriber identity module or SIM card is operatively arranged in a mobile terminal such as a GSM mobile telephone. The SIM card comprises, in accordance with the detailed description of one of the embodiments disclosed in fig. 1 or fig. 2 above, a processing device, a memory device containing a private key, an I/O device, and an interrogatable transponder.

The method starts at the initiation step 400. The method further comprises the following steps, preferably performed in the indicated order:

20 In step 410, the RFID part of the SIM card is interrogated by the external interrogating device. Upon this interrogation, as a result of the interrogation, the SIM card transmits the identification data.

25 Next, in step 420, an encrypted message is received from the external communication device. The message is encrypted with a public key associated with the identification data transmitted in the foregoing step 410. The public key is provided by the external interrogating device, preferably by a search in a database, in order to match the identification with the corresponding public key.

Next, in step 430, the encrypted message is decrypted using the private key.

Next, in step 440, the decrypted message is used as a shared key.

30 In step 450 this shared key is used to encrypt further data communication between the subscriber identity module and the external interrogating device.

Use examples

The following examples illustrate useful applications for the present invention.

Access control use

The SIM card according to the invention may be used as an authentication token for an access control system. Likewise, a mobile terminal which includes a SIM card according to the invention may also be used as an authentication token for an access control system.

- 5 In such an exemplary use scenario, a mobile phone equipped with an RFID enabled SIM card according to the invention is detected by an RFID reader at a door which is provided with an access control system. A number received by the RFID reader at the door is recognized in the access control system as a valid number, which means that the mobile telephone is a registered telephone in the access control system. The
10 access control system will then send a challenge to the phone via the GSM network. The user is asked to type a PIN number, if the PIN number is correct a signal is sent via RFID and the door is opened. In this case the user is authenticated with something he has (mobile phone with RFID tag) with something he has (PIN number).

15 *Mobile commerce use*

The SIM card according to the invention may be used as an authentication token for a mobile commerce system such as the Telenor MobilHandel. Likewise, a mobile terminal which includes a SIM card according to the invention may also be used as an authentication token for such a mobile commerce system.

- 20 In such an exemplary use scenario, a user, provided with a mobile phone equipped with an RFID enabled SIM card according to the invention, is located in front of a cash register in a commerce establishment. After deciding which good he wants to purchase, the RFID tag in the mobile phone is read by the machine, and since the machine now knows to which phone number this tag belongs to, a request for
25 purchase is sent via GSM using a M-Commerce service to the mobile phone. The user will then accept the transaction typing his PIN number, which is then sent back to the M-Commerce service and back to the cash register where the goods are dispensed.

- 30 In both above cases the RFID tag number is directly linked with the mobile phone number in a central database. So whenever the tag is detected most of the services provided by a mobile phone can potentially be used.

The SIM card according to the invention, or a mobile terminal which includes a SIM card according to the invention, may be used as an authentication token for other purposes as well.

35 *Electronic key scenario*

In an electronic key scenario, an electronic key is sent to a mobile phone through an SMS. A door is controlled by an access control system which is configured to

recognize an RFID enabled SIM card in a mobile telephone, according to the invention. The access control system is further configured to recognize the electronic key when the mobile phone is present. When the user arrives at the door, holding the mobile phone which exposes both values (key and RFID number) the door will automatically be opened.

Security and privacy use

When a mobile phone is stolen, the RFID enabled SIM card can be deactivated remotely, avoiding any possible misuse. The RFID enabled SIM card could also be deactivated through the mobile phone to avoid been detected when this is not wanted.

Business issues

The invention solves a problem for any business that wishes to adopt the RFID technology, in a way that there will not be a need to distribute RFID cards to the user, because potentially everyone with a mobile phone will already have a card.

Users will also benefit from such solution in a way that they will only need to carry their mobile phones in order to authenticate towards different services.

As most of the services offered by mobile phones, one of the biggest barriers to adopt the solution is that the market penetration has to be big enough to present an attractive alternative to already established businesses. This means that the solution should be able to function properly in all the mobile phones, and this is never an easy task.

Users will also have to renew their SIM cards, and this implies a cost for Mobile Operators.

The above detailed description has explained the invention by way of example. A person skilled in the art will realize that numerous variations and alternatives to the detailed embodiment exist within the scope of the invention, as set forth by the appended claims.



CLAIMS

1. Subscriber identity module for a mobile communication terminal, comprising a processing device, a memory device, an I/O device and a wireless communication device,
5 characterized in that said wireless communication device is an interrogatable transponder.
2. Subscriber identity module according to claim 1,
wherein said interrogatable transponder is operatively controllable by said processing device.
- 10 3. Subscriber identity module according to claim 2,
wherein the transponder is arranged to be operatively enabled or disabled, controlled by a signal provided by the mobile communication terminal via said I/O device.
4. Subscriber identity module according to claim 3,
15 wherein said signal is provided by a user interface in the mobile terminal.
5. Subscriber identity module according to claim 4,
wherein said signal is provided by a mobile communication operator.
6. Subscriber identity module according to claim 2,
wherein said interrogatable transponder comprises identification data contained in a memory, said identification data being configurable by said processing device.
20
7. Subscriber identity module according to claim 6,
wherein said identification data is provided by the mobile communication terminal via said I/O device.
8. Subscriber identity module according to claim 7,
25 wherein said identification data is provided by a mobile communication operator.
9. Subscriber identity module according to claim 3,
wherein said interrogatable transponder is arranged to transmit a RF signal coded with said identification data when interrogated by an external interrogating RF device.
- 30 10. Subscriber identity module according to one of the claims 1-9,
wherein said transponder is an active RFID transponder.
11. Subscriber identity module according to claim 10,
wherein said transponder is a separate device, comprising a processing device, a memory device and an I/O device connected to an antenna.

12. Subscriber identity module according to claim 10,
wherein said transponder comprises an antenna, and wherein further RFID
transponder functionality is implemented by means of the processing device and the
memory device included in said subscriber identity module.
- 5 13. Use of a subscriber identity module according to one of the claims 1-12, as
an authentication token.
14. Use of a subscriber identity module according to one of the claims 1-14, as
an authentication token for an access control system.
- 15 15. Use of a subscriber identity module according to one of the claims 1-12, as
an authentication token for a mobile commerce system.
- 16 Mobile communication terminal, comprising a subscriber identity module
according to one of the claims 1-12.
17. Use of a mobile communication terminal, comprising a subscriber identity
module according to one of the claims 1-12, as an authentication token.
- 15 18. Use of a mobile communication terminal, comprising a subscriber identity
module according to one of the claims 1-12, as an authentication token for an access
control system.
- 19 Use of a mobile communication terminal, comprising a subscriber identity
module according to one of the claims 1-12, as an authentication token for a mobile
commerce system.
- 20 20. Method for execution by a subscriber identity module, for the purpose of
providing secure data communication between the subscriber identity module and
an external interrogating device, said subscriber identity module comprising a
processing device, a memory device containing a private key, an I/O device, and an
interrogatable transponder,
25 said method comprising the steps of
- transmitting identification data upon an interrogation by the external interrogating
device,
- receiving an encrypted message from the external communication device, said
message being encrypted with a public key associated with said identification data,
30 - decrypting said encrypted message using said private key,
- using the decrypted message as a shared key to encrypt further data
communication between the subscriber identity module and the external
interrogating device.
- 35 21. Method according to claim 20,
wherein said public key is provided by said external interrogating device by

searching a database in order to match said identification with the corresponding public key.



ABSTRACT

The invention relates to a subscriber identity module for a mobile communication terminal, comprising a processing device, a memory device, an I/O device and a wireless communication device, in particular an interrogatable transponder such as an RFID transponder. The RFID transponder is operatively controllable by said processing device, and comprises a memory which contains identification data, configurable by the processing device. The RFID-enabled subscriber identification module may be used as an authentication token. A method for providing secure communications between the subscriber identification module and an RFID interrogating device is also provided.

Fig. 1



2004-03-31




Figure 1






Figure 2






Figure 3 Merging of RFID and GSM services






Fig. 4

